

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS Reference Number: 17676
Issue date: 26/07/2019 Revision date: 28/10/2025 Supersedes version of: 26/07/2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Product name : 04517305 UNIVERSAL SOLVENT 5L
Product code : 04517305

1.2. Relevant identified uses of the substance or mixture and uses advised against**Relevant identified uses**

Main use category : Professional use
Use of the substance/mixture : Solvents

Uses advised against

Restrictions on use : Anyone use not specified in this section or in section 7.3

1.3. Details of the supplier of the safety data sheet**Supplier**

BLINKER ESPAÑA, S.A.U.
Pol. Ind. Las Atalayas, parcelas 11, 12 y 13
03114 Alicante
Spain
T +34 966 10 25 00, F +34 966 10 25 01
msds@blinkergroup.com, www.blinkergroup.com

Distributor

BLINKER FRANCE, S.A.R.L.
Allée de Barcelone, Les Bureaux du Parc Bât. B
66350 Toulouges
France
T +33 468 68 09 74, F +33 468 55 31 99
blinkierfrance@blinkierfrance.com, www.blinkergroup.com

Distributor

BLINKER PORTUGAL, LDA.
Parque Oriente, R.D. Nuno Alvares Pereira, nº4 bl. 1 r/c
2695-167 Bobadela
Portugal
T 21 9112530, F 21 9112539
blinkier@blinkier.pt, www.blinkergroup.com

1.4. Emergency telephone number

Emergency number : ESPAÑA: 954 37 12 33 (INTCF) // PORTUGAL: 800 250 250 (CIAV) // FRANCE: 05 61 77 74 47

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 2	H225
Acute toxicity (oral), Category 4	H302
Acute toxicity (dermal), Category 4	H312
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Reproductive toxicity, Category 2	H361d
Specific target organ toxicity – single exposure, Category 1	H370
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Repeated exposure, Category 2	H373
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

GHS08

Signal word (CLP)

: Danger

Contains

: Methanol; propanone; Toluene

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.
H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H361d - Suspected of damaging the unborn child.
H370 - Causes damage to organs.
H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - Si se necesita consejo médico, tener a mano el envase o la etiqueta.
P102 - Keep out of reach of children.
P210 - Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Other hazards which do not result in classification : The product does not meet the PBT/vPvB criteria. The product does not meet the criteria for its endocrine disrupting properties.

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Toluene	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3 REACH-no: 01-2119471310-51	20 – 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
propanone	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	20 – 35	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Methanol	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X REACH-no: 01-2119433307-44	10 – 30	Flam. Liq. 2, H225 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Oral), H301 STOT SE 1, H370

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin, eyes and clothing.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propanone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Acetone
IOEL TWA	1210 mg/m ³
	500 ppm
Portugal - Occupational Exposure Limits	
Local name	Acetona
OEL TWA	500 ppm
OEL STEL	750 ppm
Spain - Occupational Exposure Limits	
Local name	Acetona
VLA-ED (OEL TWA)	1210 mg/m ³
	500 ppm
Remark	VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento.) , VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.)
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA)	1210 mg/m ³
	500 ppm
WEL STEL (OEL STEL)	3620 mg/m ³
	1500 ppm

DNEL and PNEC

Methanol (67-56-1)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	40 mg/kg bw/day
Acute - systemic effects, inhalation	260 mg/m ³
Acute - local effects, inhalation	260 mg/m ³
Long-term - systemic effects, dermal	40 mg/kg bw/day
Long-term - systemic effects, inhalation	260 mg/m ³
Long-term - local effects, inhalation	260 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	8 mg/kg bw/day
Acute - systemic effects, inhalation	50 mg/m ³
Acute - systemic effects, oral	8 mg/kg bw/day
Acute - local effects, inhalation	50 mg/m ³
Long-term - systemic effects, oral	8 mg/kg bw/day
Long-term - systemic effects, inhalation	50 mg/m ³

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methanol (67-56-1)	
Long-term - systemic effects, dermal	8 mg/kg bw/day
Long-term - local effects, inhalation	50 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	20,8 mg/l
PNEC aqua (marine water)	2,08 mg/l
PNEC aqua (intermittent, freshwater)	1540 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	77 mg/kg bw/day
PNEC sediment (marine water)	7,7 mg/kg bw/day
PNEC (Soil)	
PNEC soil	100 mg/kg bw/day
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l
propanone (67-64-1)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	2,42 mg/m ³
Acute - local effects, inhalation	2420 mg/m ³
Long-term - systemic effects, dermal	186 mg/kg KW
Long-term - systemic effects, inhalation	1210 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	62 mg/kg KW
Long-term - systemic effects, inhalation	200 mg/m ³
Long-term - systemic effects, dermal	62 mg/kg KW
PNEC (Water)	
PNEC aqua (freshwater)	10,6 mg/l
PNEC aqua (marine water)	1,06 mg/l
PNEC aqua (intermittent, freshwater)	21 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	30,4 mg/kg KW
PNEC sediment (marine water)	3,04 mg/kg KW
PNEC (Soil)	
PNEC soil	29,5 mg/kg bw/day
PNEC (Oral)	
PNEC oral (secondary poisoning)	29,5 mg/kg
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	384 mg/m ³
Acute - local effects, inhalation	384 mg/m ³
Long-term - systemic effects, dermal	384 mg/kg KW
Long-term - systemic effects, inhalation	192 mg/m ³
Long-term - local effects, inhalation	192 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	226 mg/m ³
Acute - local effects, inhalation	226 mg/m ³
Long-term - systemic effects, oral	8,13 mg/kg KW
Long-term - systemic effects, inhalation	56,5 mg/m ³
Long-term - systemic effects, dermal	226 mg/kg KW
Long-term - local effects, inhalation	56,5 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0,68 mg/l
PNEC aqua (marine water)	0,68 mg/l
PNEC aqua (intermittent, freshwater)	0,68 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	16,39 mg/kg KW
PNEC sediment (marine water)	16,39 mg/kg KW
PNEC (Soil)	
PNEC soil	2,89 mg/kg KW
PNEC (STP)	
PNEC sewage treatment plant	13,61 mg/l

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Safety glasses. Face shield. Category II. EN 166. UNE-EN ISO 18526-1. UNE-EN ISO 18526-2. UNE-EN ISO 18526-3. UNE-EN ISO 18526-4. EN ISO 4007:2018

Skin protection

Skin and body protection:

Wear suitable protective clothing. Use chemically protective clothing. Flame retardant antistatic protective clothing. Category III. EN 1149-1. EN 1149-2. EN 1149-3. EN 13034:2005+A1:2009. EN ISO 13982-1:2004/A1:2010. EN ISO 6529. EN ISO 6530. EN ISO 13688. EN 464

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection:

Protective gloves. Category III. ISO 374-1. EN 21420

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	low density polyethylene (LDPE)	6 (> 480 minutes)	0.062		

Other skin protection

Materials for protective clothing:

antistatic boots. Chemical resistant safety shoes. Heat-resistant. Category III. EN ISO 13287. EN ISO 20345. EN 13832-1

Respiratory protection

Respiratory protection:

Self-filtering mask for gases and vapors. Category III. EN 405:2002+A1:2010

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Appearance	: Transparent.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 75 °C
Flammability	: Not applicable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 10 °C
Auto-ignition temperature	: 464 °C
Decomposition temperature	: Not available
pH	: 7
Viscosity, kinematic	: < 20,5 mm ² /s (40 °C)
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 13439 Pa
Vapour pressure at 50°C	: 513,45 hPa
Density	: 823 kg/m ³
Relative density	: 0,823
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Other safety characteristics

VOC content : 821,95 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Harmful in contact with skin.
Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

04517305 UNIVERSAL SOLVENT 5L

ATE CLP (oral)	347,38 mg/kg
ATE CLP (dermal)	1042,15 mg/kg
ATE CLP (vapours)	10,42 mg/l/4h

Methanol (67-56-1)

LD50 oral rat	100 mg/kg
LD50 dermal rabbit	300 mg/kg
LC50 Inhalation - Rat	3 mg/l/4h

propanone (67-64-1)

LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	> 7400 mg/kg
LC50 Inhalation - Rat	76 mg/l/4h

Toluene (108-88-3)

LD50 oral rat	5580 mg/kg
LD50 dermal rat	12124 mg/kg
LC50 Inhalation - Rat	28,1 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
pH: 7
Serious eye damage/irritation : Causes serious eye irritation.
pH: 7
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Suspected of damaging the unborn child.
STOT-single exposure : Causes damage to organs. May cause drowsiness or dizziness.

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methanol (67-56-1)	
STOT-single exposure	Causes damage to organs.
propanone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
04517305 UNIVERSAL SOLVENT 5L	
Viscosity, kinematic	< 20,5 mm ² /s (40 °C)

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

04517305 UNIVERSAL SOLVENT 5L	
Persistence and degradability	Rapidly degradable
Methanol (67-56-1)	
Persistence and degradability	Rapidly degradable
propanone (67-64-1)	
Persistence and degradability	Rapidly degradable
Toluene (108-88-3)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR) : UN 1263
UN-No. (IMDG) : UN 1263
UN-No. (IATA) : UN 1263
UN-No. (ADN) : UN 1263
UN-No. (RID) : UN 1263

14.2. UN proper shipping name

Proper Shipping Name (ADR) : PAINT RELATED MATERIAL
Proper Shipping Name (IMDG) : PAINT RELATED MATERIAL
Proper Shipping Name (IATA) : Paint related material
Proper Shipping Name (ADN) : PAINT RELATED MATERIAL
Proper Shipping Name (RID) : PAINT RELATED MATERIAL
Transport document description (ADR) (ADR) : UN 1263 PAINT RELATED MATERIAL, 3, II, (D/E)
Transport document description (IMDG) : UN 1263 PAINT RELATED MATERIAL, 3, II
Transport document description (IATA) : UN 1263 Paint related material, 3, II
Transport document description (ADN) : UN 1263 PAINT RELATED MATERIAL, 3, II
Transport document description (RID) : UN 1263 PAINT RELATED MATERIAL, 3, II

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



ADN

Transport hazard class(es) (ADN) : 3
Danger labels (ADN) : 3



RID

Transport hazard class(es) (RID) : 3
Danger labels (RID) : 3



14.4. Packing group

Packing group (ADR) : II
Packing group (IMDG) : II
Packing group (IATA) : II
Packing group (ADN) : II
Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 163, 367, 640D, 650
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001, IBC02, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1, TP8, TP28
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation (ADR) : S2, S20
Hazard identification number (Kemler No.) : 33
Orange plates :



Tunnel restriction code (ADR) : D/E
EAC code : •3YE

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Transport by sea

Special provisions (IMDG)	: 163, 367
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8, TP28
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 640D, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E2
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 640D, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP28
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 821,95 g/l

Explosives Precursors Regulation (EU 2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Drug Precursors Regulation (EC 273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I
Toluene		108-88-3	2902 30 00	Category 3		Annex I

National regulations

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
Chemicals Prohibition Ordinance (ChemVerbotsV) : This product is subject to ChemVerbotsV Annex 2 Entry 1. The following requirements must be observed: authorization requirement (according to § 6 paragraph 1 sentence 1), basic requirements for carrying out the delivery (according to § 8 paragraph 1, 3 and 4), identification and documentation (according to § 9 paragraph 1 to 3) and exclusion of the shipping route (according to § 10).

VOC content : 821,95 g/l

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Netherlands

SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: Toluene is listed

Denmark

Class for fire hazard	: Class I-1
Store unit	: 1 liter
Classification remarks	: F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with it. If an employee is pregnant or breastfeeding and the person in question uses or is exposed to this product at work, the employer must always carry out a risk assessment of the work. The assessment must both deal with the dangerousness of the impact and its strength and duration. The employer's decision that a pregnant or lactating woman can perform a specific work task must therefore be made in the context of her specific working conditions. See also WEA-Guideline A.1.8-7 on the working environment of pregnant and breastfeeding workers.

Poland

Polish National Regulations	: Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225). Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797). The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended). Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923). Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154). Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended). The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488) Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended). Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141). ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891) Regulation of the Minister of Health of 25 August 2015 on the method of marking places, pipelines, and containers and tanks used for storing or containing hazardous substances or hazardous mixtures (J.o.L. 2015, item 1368 as ammended)
-----------------------------	--

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

04517305 UNIVERSAL SOLVENT 5L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 1	Specific target organ toxicity – single exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.